



P.O. Box 554, Portland, OR; 97207  
503-292-8682(Phone) 800-722-8078 503-292-8697(Fax)

Website: [www.pr-tech.com](http://www.pr-tech.com)  
[www.prtech-thermalimaging.com](http://www.prtech-thermalimaging.com)

---

## Met Tower FireFly Fixed Model

**High Winds – Collision Prevention Only.**

Uses drop forged galvanized wire rope clip, which is made for ¼ “ met tower guy wire attachment with stainless steel nylock threaded nut. Diamond bar florescent yellow and orange reflective stickers rated by manufacturer for 10 year. Phosphorescent stickers will glow for 10-12 hours after sunset for nocturnally migrating birds and bats. 1 year manufacturer’s warranty for parts and labor. Ultraviolet inhibited acrylic plastic flapper – dimensions –3.5” by 7.0 “ rectangular cut. Clear coat finish available for increased life span of diverter in arctic or coastal conditions. For met towers less than 100 feet in height.

Product Use – Collision prevention product only.... Not to be used for hazing birds. Long term installation in inaccessible areas on met and radio tower guys 100 feet in height or greater. Guy wires must have minimal ¼ “diameter. Installs easily with portable drill and snap on socket to fit nylock nut. Install at 10 meter (30 feet ) spacing.

For smooth wire or spiral wrap guy wires greater than ¼”

