



SLATERCOM- WCD UCS SERIES LIGHTING CONTROLLER

DESIGNED SPECIFICALLY FOR LED LIGHTING SYSTEMS

- AVAILABLE IN ANY AC OR DC VERSION
- FAA A-0 THRU A-3 MODELS AVAILABLE
- ISOLATED REGULATED POWER SUPPLY
- DESIGNED FOR LED SYSTEMS
- INCANDESCENT MODELS AVAILABLE
- ALL INTERCONNECTION THRU DIN TERMINALS
- SEPARATE ALARM TERMINAL STRIP
- LED'S INDICATE "NORMAL" & "ALARM"
- ALL INPUTS & OUTPUTS FUSED
- LED'S ON FUSE HOLDERS SHOW OPEN FUSES
- EASILY SERVICED MODULAR CONSTRUCTION
- LOCKABLE NEMA 4X FIBERGLASS ENCLOSURE
- STANDARD FG ENCLOSURE-10" w X12"h X8"d
- SHIPPING WEIGHT- 10 LBS OR LESS
- POWDER COATED AND STAINLESS STEEL AVAILABLE
- MANUAL PEC OVERRIDE PROVIDED
- ALARM RELAYS CONFIGURABLE AS NO OR NC
- OPERABLE OVER FAA SPECIFIED - 55C TO +55C TEMPERATURE
- SYSTEM SCHEMATIC & ID LABELS LOCATED ON INSIDE DOOR
- ALL I/O CONNECTIONS PROTECTED TO FAA AC150/5345-43E SPEC
- FIVE YEAR WARRANTY
- CUSTOM CONFIGURATIONS READILY AVAILABLE



48VDC CONTROLLER SHOWN